



ESD TORQUE Screwdrivers

45-070-0060 to -0061

High quality screwdrivers for safe use on sensitive electronic components.

Technical data:

Surface resistance: $< 1 \times 10^9 \Omega$
Application standards: IEC 61340-2-3

REACH-compliant

Stainless steel torque screwdrivers from Wera

Torque tool with adjustable torque of 2.0 to 6.0 cNm (accuracy $\pm 10\%$). Compact handle/interchangeable blade system for torque controlled precision screwdriving. The Kraftform Micro ESD torque screwdriver is ideal for torque controlled jobs on electrostatically-susceptible components. Suitable for the take-up of bits with 4 mm halfmoon drive (Wera series 9) and 4 mm HIOS drive (Wera series 21).

Tamperproof. Distinct audible and perceivable excess load signal when the pre-set torque value is reached. Unlimited manual loosening torque. Electrical surface resistance of $\leq 10^9 \text{ Ohm}$ for secure protection against electrostatic charge.

Manufactured in accordance with DIN EN 61340-5-1. Handle/Interchangeable blade system for rapid blade change. Kraftform Micro handle with twist cap and free-turning zone for rapid twisting, making any time-consuming repositioning of the fingers unnecessary. Power zone with integrated soft zones for the transfer of higher tightening and loosening torque. Precision zone directly above the blade for the right angle for adjustment work. Rapid fixing of the bit: just push the bit into the insert for automatic locking and a secure fit. To change the bit, simply push the sleeve forward and remove. Free-turning sleeve for simple guidance of the tool during the screwdriving process. Bits suitable for manual as well as power tool operations with electric screwdrivers (e.g. HIOS, Delvo, Sehan). Applications for example on smartphones, cell phones, cameras, electrical appliances, in dental labs and dental surgeries.



Features	Picture	Part nr
Model nr: Wera 1430 TORQUE BITS tip: 4mm - 0,02-0,06Nm 		45-070-0060
Model nr: Wera 1431 TORQUE BITS tip: 4mm - 0,05-0,11Nm 		45-070-0061